

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

### 1 Identification

- **Product identifier**
- **Trade name:** POLYASPARTIC FLOOR GREY
- **Article number:** 103002
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Wasser Corporation  
4118 B PL NW, Suite B  
Auburn, WA 98001, US  
Phone 253-850-2967
- **Information department:** Product safety department
- **Emergency telephone number:**  
EMERGENCY PHONE NUMBERS:  
USA and Canada: 1-800 424-9300  
International: 1-703 527-3887

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 Mutagen. 1B H340 May cause genetic defects.  
 Carc. 1B H350 May cause cancer.



Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.  
 Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

Flam. Liq. 4 H227 Combustible liquid.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane  
 Isophorodiamine-isobutyraldimine  
 titanium dioxide  
 Solvent naphtha (petroleum), light arom.

(Contd. on page 2)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

**Trade name: POLYASPARTIC FLOOR GREY**

(Contd. of page 1)

**· Hazard statements**

H227 Combustible liquid.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

**· Precautionary statements**

Keep out of reach from children.

P210 Keep away from flames and hot surfaces. – No smoking.

P260 Do not breathe dusts or mists.

P284 [In case of inadequate ventilation] wear respiratory protection.

P280 Wear protective gloves / eye protection / face protection.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Classification system:**

**· NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 2

Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**

HEALTH	*3
FIRE	2
REACTIVITY	0

Health = \*3

Fire = 2

Reactivity = 0

**· Other hazards**

**· Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

**· Chemical characterization: Mixtures**

**· Description:** Mixture of the substances listed below with nonhazardous additions.

**· Dangerous components:**

136210-32-7 bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane

30-60%

(Contd. on page 3)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

**Trade name: POLYASPARTIC FLOOR GREY**

(Contd. of page 2)

136210-30-5	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	30-60%
54914-37-3	Isophorodiamine-isobutyraldimine	5-10%
13463-67-7	titanium dioxide	5-10%
623-91-6	diethyl fumarate	1-5%
7727-43-7	barium sulphate, natural	1-5%
1333-86-4	Carbon black	0.1-1%
64742-95-6	Solvent naphtha (petroleum), light arom.	0.1-1%

**4 First-aid measures**

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

US

(Contd. on page 4)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

**Trade name: POLYASPARTIC FLOOR GREY**

(Contd. of page 3)

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
  - Ensure good ventilation/exhaustion at the workplace.
  - Open and handle receptacle with care.
  - Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
  - Keep ignition sources away - Do not smoke.
  - Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

**7727-43-7 barium sulphate, natural**

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 5* mg/m <sup>3</sup> *inhalable fraction; E

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

During mixing, handling and application: Splash goggles. Full protective clothing. Gloves (impervious). Wear suitable respiratory equipment. When air concentrations are not known (or above the TLV), an air-supplied respirator is required. Refer to OSHA Respiratory Protection Standard (29 CFR 1910.134). In presence of air movement, air-purifying (cartridge type) respirators are not the best protection but can be used, if you replaced them frequently. Change cartridges after 8h max or less due to their low warning properties. When in a confined space wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

**Trade name: POLYASPARTIC FLOOR GREY**

(Contd. of page 4)

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

**• Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

**• Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

**• Eye protection:**



*Tightly sealed goggles*

## 9 Physical and chemical properties

<b>• Information on basic physical and chemical properties</b>	
<b>• General Information</b>	
<b>• Appearance:</b>	
<b>Form:</b>	Fluid
<b>Color:</b>	Grey
<b>• Odor:</b>	slight
<b>• Odor threshold:</b>	Not determined.
<b>• pH-value:</b>	Not determined.
<b>• Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	218 °C (424 °F)
<b>• Flash point:</b>	86 °C (187 °F)
<b>• Flammability (solid, gaseous):</b>	Not applicable.
<b>• Ignition temperature:</b>	310 °C (590 °F)
<b>• Decomposition temperature:</b>	Not determined.
<b>• Auto igniting:</b>	Product is not selfigniting.
<b>• Danger of explosion:</b>	Not determined.
<b>• Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>• Vapor pressure:</b>	Not determined.
<b>• Density at 20 °C (68 °F):</b>	1.11 g/cm³ (9.263 lbs/gal)
<b>• Relative density</b>	Not determined.
<b>• Vapor density</b>	Not determined.
<b>• Evaporation rate</b>	Not determined.
<b>• Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
<b>• Partition coefficient (n-octanol/water):</b>	Not determined.

(Contd. on page 6)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

**Trade name: POLYASPARTIC FLOOR GREY**

(Contd. of page 5)

<b>· Viscosity:</b>	
<b>Dynamic:</b>	<i>Not determined.</i>
<b>Kinematic:</b>	<i>Not determined.</i>
<b>· Solvent content:</b>	
<b>Solids content:</b>	<i>100.0 %</i>
<b>Other information</b>	<i>No further relevant information available.</i>

## 10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** *Caustic effect on skin and mucous membranes.*

- **on the eye:**

*Strong caustic effect.*

*Strong irritant with the danger of severe eye injury.*

- **Sensitization:**

*Sensitization possible through inhalation.*

*Sensitization possible through skin contact.*

- **Additional toxicological information:**

*The product shows the following dangers according to internally approved calculation methods for preparations:*

*Harmful*

*Corrosive*

*Irritant*

*Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.*

*The product can cause inheritable damage.*

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

(Contd. on page 7)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

### Trade name: POLYASPARTIC FLOOR GREY

(Contd. of page 6)

14808-60-7	Quartz ( $SiO_2$ )	1
111-76-2	2-butoxyethanol	3
· <b>NTP (National Toxicology Program)</b>		
14808-60-7	Quartz ( $SiO_2$ )	K
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

### 12 Ecological information

· **Toxicity**

· **Aquatic toxicity**: No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems**:

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information**:

· **General notes**:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT**: Not applicable.

· **vPvB**: Not applicable.

· **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings**:

· **Recommendation**: Disposal must be made according to official regulations.

### 14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA**

UN3066

· **UN proper shipping name**

· **DOT, IATA**

Paint

· **ADR**

3066 Paint

· **IMDG**

PAINT

· **Transport hazard class(es)**

· **DOT**



· **Class**

8 Corrosive substances

· **Label**

8

(Contd. on page 8)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

**Trade name: POLYASPARTIC FLOOR GREY**

(Contd. of page 7)

<b>· ADR, IMDG, IATA</b>	
<b>· Class</b>	8 Corrosive substances
<b>· Packing group</b>	
<b>· DOT, ADR, IMDG, IATA</b>	III
<b>· Environmental hazards:</b>	Not applicable.
<b>· Special precautions for user</b>	Warning: Corrosive substances
<b>· EMS Number:</b>	F-A,S-B
<b>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
<b>· Transport/Additional information:</b>	
<b>· ADR</b>	
<b>· Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>· UN "Model Regulation":</b>	UN 3066 PAINT, 8, III

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Sara**

- Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):**

7727-43-7	barium sulphate, natural
-----------	--------------------------

1330-20-7	xylene
-----------	--------

100-41-4	ethylbenzene
----------	--------------

111-76-2	2-butoxyethanol
----------	-----------------

- TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- Proposition 65**

- Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
------------	------------------

1333-86-4	Carbon black
-----------	--------------

100-41-4	ethylbenzene
----------	--------------

14808-60-7	Quartz (SiO <sub>2</sub> )
------------	----------------------------

- Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- Carcinogenic categories**

- EPA (Environmental Protection Agency)**

7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
1330-20-7	xylene	I

(Contd. on page 9)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

**Trade name: POLYASPARTIC FLOOR GREY**

(Contd. of page 8)

100-41-4	ethylbenzene	D
111-76-2	2-butoxyethanol	NL

**· TLV (Threshold Limit Value established by ACGIH)**

titanium dioxide	A4
Carbon black	A4

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz ( $SiO_2$ )

**· GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**



GHS05 GHS08

**· Signal word Danger**

**· Hazard-determining components of labeling:**

bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane

Isophorodiamine-isobutyraldimine

titanium dioxide

Solvent naphtha (petroleum), light arom.

**· Hazard statements**

H227 Combustible liquid.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

**· Precautionary statements**

P210 Keep away from flames and hot surfaces. – No smoking.

P260 Do not breathe dusts or mists.

P284 [In case of inadequate ventilation] wear respiratory protection.

P280 Wear protective gloves / eye protection / face protection.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

(Contd. on page 10)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/13/2016

Reviewed on 01/06/2016

### Trade name: POLYASPARTIC FLOOR GREY

P501 (Contd. of page 9)  
*Dispose of contents/container in accordance with local/regional/national/international regulations.*

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**  
*Carcinogenic hazardous material group III (dangerous).*
- **Information about limitation of use:**  
*Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Product safety department

· **Contact:** HS REG.DEPART.REG.SS

· **Date of preparation / last revision** 01/13/2016 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Muta. 1B: Germ cell mutagenicity, Hazard Category 1B

Carc. 1B: Carcinogenicity, Hazard Category 1B

US